

ENOSLOJNA KOGENERACIJA - enoslojni dimniški sistemi za kogeneracijske naprave (nadtlačno delovanje do 5000 Pa)



Naziv	Cev 1000mm	Cev 500mm	Cev 330mm	Cev 250mm	Cev 200mm	Cev 150mm	Cev 1000mm z zanko za sanacijo	Cev 1000mm z montažnim distančnikom
Koda	KL0602	KL0603	KL06222	KL0604	KL06223	KL06224	KL0605	KL0670
Ø80	26,39	16,34	17,59	10,05	10,05	8,80	28,90	42,72
Ø100	31,42	18,85	22,62	16,34	16,34	15,08	33,93	45,24
Ø120	35,18	21,36	23,88	17,59	17,59	16,34	37,70	47,75
Ø130	40,21	23,88	23,88	15,08	17,59	16,34	41,47	47,75
Ø150	45,24	26,39	25,13	16,34	17,59	16,34	47,75	50,26
Ø180	51,52	31,42	30,16	18,85	21,36	20,11	54,03	57,80
Ø200	57,80	35,18	30,16	21,36	22,62	21,36	60,32	62,83
Ø225	64,09	37,70	33,93	23,88	23,88	22,62	67,86	69,11
Ø250	71,63	42,72	37,70	25,13	25,13	23,88	74,14	76,65
Ø300	87,96	52,78	37,70	31,42	28,90	27,65	90,48	87,96
Ø350	109,32	66,60	46,49	40,21	32,67	31,42	111,84	99,27
Ø400	135,71	82,94	54,03	49,01	37,70	36,44	138,23	110,58
Ø450	163,36	98,01	64,09	59,06	41,47	40,21	165,87	124,40
Ø500	189,75	114,35	70,37	69,11	47,75	46,49	192,26	145,77
Ø600	243,78	147,02	95,50	87,96	67,86	66,60	246,29	191,00

ODVODI KONDENZA



Naziv	Nastavljiva cev 320-480 mm s tesnilom in objemko; do 200°C	Nastavljiva cev 320-480 mm z objemko; do 400°C	Cev 250mm z odvodom kondenza s 1/2" niplom - vert./horiz.vgradnja	Odvod kondenza s cevko l=250mm	Odvod kondenza s cevko l=250mm +½" mufna	Odvod kondenza s cevko l=250mm +½" niipel
Koda	KL06114D	KL06114	KL06110	KL01	KL01A	KL01B
Ø80	67,86	56,55	101,78	28,90	59,06	42,72
Ø100	67,86	56,55	103,04	30,16	60,32	43,98
Ø120	69,11	56,55	104,30	31,42	61,57	45,24
Ø130	71,63	59,06	105,55	32,67	61,57	45,24
Ø150	76,65	62,83	106,81	32,67	62,83	46,49
Ø180	87,96	74,14	110,58	33,93	64,09	47,75
Ø200	95,50	80,42	113,09	36,44	70,37	50,26
Ø225	101,78	85,45	115,61	40,21	70,37	52,78
Ø250	105,55	89,22	116,86	42,72	72,88	55,29
Ø300	134,46	116,86	123,15	45,24	75,40	57,80
Ø350	149,54	128,17	124,40	52,78	82,94	66,60
Ø400		134,46	130,69	61,57	92,99	75,40
Ø450		148,28	138,23	74,14	104,30	86,71
Ø500		158,33	148,28	76,65	106,81	89,22
Ø600		189,75	175,92	103,04	133,20	115,61

ENOSLOJNA KOGENERACIJA - enoslojni dimniški sistemi za kogeneracijske naprave (nadtlačno delovanje do 5000 Pa)



Naziv	Vrataca velika z nastavkom	Vrataca velika gola	Čistilni kos vgradni; do 400°C	Čistilni kos do 200°C/200Pa	Čistilni kos do 400°C	Čistilni kos do 600°C/5000 Pa
Koda	FU0960	FU13	KL0607	KL0630	KL0607R	KL0630HT
Ø80	dim.210x140mm	dim.210x140mm	33,93	76,65	69,11	196,03
Ø100			33,93	82,94	69,11	177,18
Ø120	51,64	43,36	35,18	90,48	72,88	216,14
Ø130			36,44	95,50	77,91	216,14
Ø150			40,21	98,01	79,17	250,06
Ø180			43,98	105,55	79,17	296,56
Ø200			50,26	111,84	95,50	304,10
Ø225			52,78	119,38	100,53	375,72
Ø250			59,06	124,40	118,12	384,52
Ø300			70,37	109,32	109,32	388,29
Ø350			84,19	162,10	129,43	471,23
Ø400			104,30	150,79	150,79	495,10
Ø450			119,38	209,85	167,13	520,23
Ø500			130,69	241,27	184,72	580,55
Ø600			175,92	290,27	219,91	635,84

PRIKLJUČNI KOSI



Naziv	T- kos 87°	T- kos 87° prikluček FU	T- kos 45°	T-kos 45° prikluček FU	Koleno 87° s podporo	Koleno 87° s podporo, prikluček FU
Koda	KL0608	KL06117	KL0623	KL06118	KL0606	KL06276
Ø80	50,26	50,26	79,17	79,17	75,40	75,40
Ø100	50,26	50,26	82,94	82,94	77,91	77,91
Ø120	54,03	54,03	94,25	94,25	81,68	81,68
Ø130	56,55	56,55	98,01	98,01	84,19	84,19
Ø150	64,09	64,09	108,07	108,07	87,96	87,96
Ø180	81,68	81,68	124,40	124,40	108,07	108,07
Ø200	85,45	85,45	126,92	126,92	128,17	128,17
Ø225	92,99	92,99	135,71	135,71	138,23	138,23
Ø250	100,53	100,53	139,48	139,48	159,59	159,59
Ø300	108,58	109,32	160,84	160,84	191,00	191,00
Ø350	74,42	120,63	163,36	163,36	217,39	217,39
Ø400	130,69	130,69	168,38	168,38	245,04	245,04
Ø450	136,97	136,97	187,23	187,23	283,99	283,99
Ø500	162,10	162,10	211,11	211,11	345,57	345,57
Ø600	218,65	218,65	285,25	285,25	456,15	456,15

KOLENA



Naziv	Koleno 15°	Koleno 30°	Koleno 45°	Koleno 87°	Koleno 90°	Koleno 87° s čistilno odprtino - do 400°C
Koda	KL0609	KL0610	KL0611	KL0612	KL0613	KL0614
Ø80	15,08	15,08	15,08	26,39	26,39	42,72
Ø100	15,08	15,08	15,08	28,90	28,90	45,24
Ø120	16,34	16,34	16,34	31,42	31,42	47,75
Ø130	17,59	17,59	17,59	32,67	32,67	49,01
Ø150	18,85	18,85	18,85	36,44	36,44	52,78
Ø180	22,62	22,62	22,62	51,52	51,52	67,86
Ø200	26,39	26,39	26,39	66,60	66,60	81,68
Ø225	31,42	31,42	31,42	74,14	74,14	89,22
Ø250	36,44	36,44	36,44	89,22	89,22	105,55
Ø300	55,29	55,29	55,29	110,58	110,58	139,48
Ø350	57,80	57,80	57,80	130,69	130,69	160,84
Ø400	66,60	66,60	66,60	153,31	153,31	177,18
Ø450	72,88	72,88	72,88	180,95	180,95	198,54
Ø500	84,19	84,19	84,19	212,37	212,37	233,73
Ø600	110,58	110,58	110,58	290,27	290,27	319,18



Naziv	Koleno 90° s čistilno odprtino, do 400°C	Koleno 87° s čistilno odprtino in tesnilom, do 200°C / 200Pa	Koleno 90° s čistilno odprtino in tesnilom, do 200°C / 200Pa	Koleno 87° s čistilno odprtino, do 600°C / 5000Pa	Koleno 90° s čistilno odprtino, do 250°C / 5000Pa
Koda	KL0615	KL0614D	KL0615D	KL0623HT	KL0624HT
Ø80	42,72	49,01	49,01	121,89	121,89
Ø100	45,24	51,52	51,52	124,40	124,40
Ø120	47,75	54,03	54,03	126,92	126,92
Ø130	49,01	55,29	55,29	128,17	128,17
Ø150	52,78	60,32	60,32	131,94	131,94
Ø180	67,86	76,65	76,65	147,02	147,02
Ø200	81,68	91,73	91,73	160,84	160,84
Ø225	89,22	100,53	100,53	168,38	168,38
Ø250	105,55	116,86	116,86	184,72	184,72
Ø300	139,48	152,05	152,05	218,65	218,65
Ø350	160,84	177,18	177,18	240,01	240,01
Ø400	177,18	192,26	192,26	256,35	256,35
Ø450	198,54	214,88	214,88	277,71	277,71
Ø500	233,73	256,35	256,35	312,89	312,89
Ø600	319,18	343,05	343,05	398,34	398,34